

MTI SERVICE NOTICE

SAFE-T-ALERT™ REPLACEMENT CROSS LIST

MTI Industries, Inc. has a number of direct replacement propane alarms for the CCI Controls models. Refer to the cross list guide below. These are direct replacement units and no modifications are required.

CCI PROPANE ALARM MODEL SAFE-T-ALERT PROPANE ALARM MODEL

7770.230	30-442-P-AL
7770.231	30-442-P-BR
7770.234	30-442-P-WT
7770.241	30-441-P-BR
7770.244	30-441-P-WT
7770.281	30-442-P-BR
7770-284	30-442-P-WT

NOTE: Some CCI units installed in Fleetwood and Winnebago RV's have two power leads. Safe-T-Alert units only have one power lead. Connect the "House" power to the Safe-T-Alert Red wire and cut and cap the "Chassis" power wire.

7773.081	30-442-P-BR
7773.231	30-442-P-BR
7773.151	30-442-P-BR
7773.251	30-442-P-BR

NOTE: The 30-442 series can be installed both vertically and horizontally.

SOLONOID VALVE

WARNING - DO NOT connect any Safe-T-Alert propane alarm to any solenoid valve controlled by a CCI propane alarm. A burn or fire danger can occur using Safe-T-Alert propane alarms and CCI solenoid valves. The CCI 7719 and valve **MUST** be removed and replaced by a Safe-T-Alert 70-742-R-KIT.

CCI PROPANE ALARM W/SOLONOID	SAFE-T-ALERT PROPANE ALARM W/SOLONOID
7719.04	70-742-R-KIT-BR
7719.14	NA *
7719.47	NA *
7719.7	70-742-R-KIT-BR

IMPORTANT: The 70-742-R-KIT flush mount case dimensions are 6.5" W x 3.5" H x 1 3/8" D. A 4" W x 3" H cut out is required with a 1 3/8" clearance for the case.

* Not Available

COMBINATION PROPANE AND CARBON MONOXIDE ALARM

The Safe-T-Alert 35 series combination propane and CO alarm is a direct replacement for all Safe-T-Alert 30-442 and all CCI propane alarms that can be replaced with a 30-442 alarm. The 35 series is an ideal solution to replace both alarms with one easy to install product. Many older RV's have propane alarms but not CO alarms. The 35 series is the solution to add a CO alarm when replacing the propane alarm.

35-742-AL	Almond
35-742-BR	Brown
35-742-BL	Black
35-742-WT	White